

Industrial Series Flow Meters

FPP flow meters are available with either mechanical or electronic registers, and can be assembled to suit the most demanding operational requirements. Electronic assemblies are gland-less, and can have the display either mounted or remote.



Materials & Performance:

- +/- 0.3% Over 10:1 Turndown & +/- 0.05% Repeatability
- Flow Rates to 200 GPM (760 lpm)
- Mechanical or Electronic Registers, with Optional Preset & Printing Functions
- 1", 1½", 2" & 3" Models
- Companion Flanges Standard, 150# RF ANSI Adaptors Optional
- Anodized Aluminum or Stainless Steel
- PPS Rotors with Carbon or Teflon™ Bearings
- Viton™ or Teflon™ Seals
- 400 PSI (28 BAR) MWP with Electronic Register
- 150 PSI (10.5 BAR) MWP with Mechanical Register
- Complete Range of Accessories
 - Strainer & Air Eliminator
 - Mechanical Preset Valve with Linkage
 - 1-Stage & 2-Stage Solenoid Valve

Available Options & Accessories:

Options and accessories available with TS Series meters can best be understood by referring to the [TUTHILL TS Series assembly options chart](#). When selecting a flow meter with electronic register, the register is usually specified as a separate item from the flow meter. Please consult with your distributor for complete details.

Repair & Maintenance:

Refer to the Installation & Maintenance Manual supplied with each flow meter. For installation & calibration assistance, please contact your distributor.